



TOUGH-GUY OIL CONTAINMENT BOOM SPECIFICATIONS

Fabric: 22oz. nominal PVC coated polyester	
Base Fabric (100% Polyester)	1500x1500 denier 16x16 threads/sq in
Weight (FS-191-5041)	22oz./yard ²
Tensile Strength, Grab (ASTMD751-A)	500 lbs x 500 lbs
Tear Strength, Tongue (ASTMD5884)	145 lbs x 145 lbs
Adhesion Strength (ASTM 751)	17x17 lbs/inch
Cold Crack Resistance (ASTM 2136) -40°F	

High Temp, Cont/interm. (ASTMD1204) 160/180°F

All seams heat sealed

5/16" galvanized steel 7x19 load cable with PVC coating in top, 10,000 lb. break strength. No cable on 10" boom.

5/16" galvanized chain ballast on 18" & 24" Booms, 1/4" chain on 10" Boom

ASTM compliant universal end connectors

Polyethylene Foam Log, 6 Feet Long X 4", 6", Or 8" Diameter Depending On Boom Height

3/8" ASTM locking pin with lanyard



MADE IN THE USA

SOLD ONLY BY AER-FLO DISTRIBUTORS

PH: 941.747.4151 | AerFloEnv.com